


TECHNICAL DATA

BOMAG VARIOCONTROL (BVC)

BW 213 BVC-5





Dimensions in mm

	A	B	D	H	H2	K	L	O1	O2	S	W
BW 213 BVC-5	2975	2270	1500	2250	2990	490	5870	70	70	30	2130

Shipping dimensions in m3

BW 213 BVC-5

without ROPS

29,981

with ROPS

39,841

Machine type	Compaction output (m3/h)			
	Rock fill	Gravel, sand	Mixed soil	Silt, clay
BW 213 BVC-5	700-1400	480-960	360-720	210-420

Machine type	Compacted layer thickness (m)			
	Rock fill	Gravel, sand	Mixed soil	Silt, clay
BW 213 BVC-5	1,20	0,80	0,60	0,30

Technical Data

BOMAG BW 213 BVC-5

Weights

Grossweight	kg	16.170
Operating weight CECE w. ROPS-cabin	kg	13.820
Axle load, drum CECE	kg	8.500
Axle load, wheels CECE	kg	5.320
Static linear load CECE	kg/cm	39,9

Dimensions

Working width	mm	2.130
Track radius, inner	mm	3.680

Driving Characteristics

Speed	km/h	0- 12,0
Max. gradeability without/with vibr.	%	58/55

Drive

Engine manufacturer		Deutz
Type		TCD 4.1 L4
Emission stage		Stage V / TIER4f
Exhaust gas aftertreatment		DOC+DPF+SCR
Cooling		Liquid
Number of cylinders		4
Performance ISO 3046	kW	115,0
Performance SAE J 1995	hp	155,0
Speed	min-1	2.100
Fuel		Diesel
Electric equipment	V	12
Drive system		hydrost.
Drum driven		standard

Drums and Tyres

Tyre size	23.1-26 12PR
-----------------	--------------

Brakes

Service brake	hydrost.
Parking brake	hydromec.

Steering

Steering system		oscil.artic.
Steering method		hydrost.
Steering / oscillating angle +/-	grad	35/12

Exciter system

Drive system		hydrost.
Frequency (1)	Hz	28
Amplitude (1)	mm	0 - 2,25
Centrifugal force 1	kN	365
Centrifugal force 1	t	37,2

Capacities

Fuel	l	250,0
------------	---	-------

Technical modifications reserved. Machines may be shown with options.

Standard Equipment

- ☒ BOMAG ECOMODE
- ☒ BOMAG VARIOCONTROL
- ☒ TERRAMETER
- ☒ Oscillation mode
- ☒ Warning, information and operation displays with LCD
- ☒ Hydrostatic travel and vibration drive
- ☒ Hydrostatic articulated steering
- ☒ Articulated joint lock
- ☒ Rear axle with twin spring accumulator brakes
- ☒ Self locking differential
- ☒ Warning horn
- ☒ Single lever control for travel and vibration
- ☒ Seat with arm rest and adj. for position and height
- ☒ 2 Scrapers
- ☒ Emergency STOP
- ☒ Back-up alarm
- ☒ Working lights front / rear
- ☒ Double pump system for travel drive
- ☒ TERRAMETER
- ☒ Loading mode
- ☒ Battery disconnect switch
- ☒ BOMAG TELEMATIC POWER

Optional Equipment

- ☐ * ROPS/FOPS cabin with seat belts
 - Sliding window
- ☐ Air condition
- ☐ Rearview camera
- ☐ BOMAG ECOSTOP
- ☐ Padfoot segment kit
- ☐ Radio (Bluetooth)
- ☐ Indicator and hazard lights
- ☐ Special painting
- ☐ Rotary beacon
- ☐ Pre start cabin heating
- ☐ Environmentally compliant hydraulic oil
- ☐ Comfort package: Adjustable seat and adjustable steering column
- ☐ Measuring- and machine data interface for third-party suppliers
- ☐ LED Working lights (Cabin)
- ☐ Highly wear resistant drum
- ☐ Reversing alarm buzzer with broad band audio

* Standard delivery with CE conformity
(valid within European Union)#72

